


**Dual Fiber 8CH 1470-1610nm CWDM MUX DEMUX With EXP and Monitor Port, LC/UPC, Plug-in LGX Box and 2slot 1U Rack**



The 8ch CWDM MUX DEMUX is designed by FIBERWDM, wavelength from 1470nm to 1610nm, and it is passive CWDM and plug-in LGX box, can plug in 2slot 1u rack, support 8channels difference business in two optical fiber for point-to-point transmission.

It works in Broadcast and TV, IDC, finance, government, cloud, massive data and other industries, where the optical fiber resource are rare.


**Product Panel**



**8CH CWDM MUX DEMUX Dual Fiber**

Expansion Port for Future Bandwidth Increasing, makes it possible to increase the network capacity by connecting it to the line port of another CWDM MUX/DEMUX supporting different wavelengths, without the need of installing or leasing additional fibers.

**Line Link**



**8CH CWDM MUX DEMUX Dual fiber transmission**


8Channels CWDM MUX DEMUX, support 8 channels difference business, such applications as 1G/10G Ethernet, SDH/SONET and 8/4/2/1G, in two optical fiber for point-to-point transmission.

**Product Specification**

<b>Wavelength</b>	8 channels 1470-1610nm	<b>Channel Spacing</b>	20nm
<b>Channel Passband</b>	±6.5nm	<b>Technology</b>	TFF (Thin Film Filter)
<b>Insertion Loss</b>	Regular :≤ 2.4dB	<b>Link Loss</b>	≤ 2.4dB
<b>Insertion Loss @ 1% Mon</b>	≤ 26dB	<b>Center Wavelength Accuracy</b>	±0.05nm
<b>Return Loss</b>	≥ 45dB	<b>Directivity</b>	≥ 45dB
<b>Polarization Mode Dispersion</b>	≤ 0.1ps	<b>Polarization Dependent Loss</b>	≤ 0.3dB
<b>Channel Isolation</b>	Adjacent ≥30dB Non-adjacent ≥ 45dB	<b>Temperature</b>	Operating -40 to 85°C Storage -40 to 85°C
<b>Net Weight</b>	LGX BOX 0.5KG 2Slot 1u Rack 2.5KG	<b>Dimensions (HxWxD)</b>	LGX BOX 190*200*39mm 2Slot 1u Rack 44*440*230mm

Note: Specified with connectors.

**Package Information**



**Plug-in LGX Box**



**2-Slot 1U Rack for LGX BOX**

**Order Information**

Product No.	Product description
CMD8-1U01-4761M	CWDM MUX DEMUX 8CH (1470nm~1610nm) With EXP And Monitor Port, Dual fiber, LC/UPC , Plug-in LGX Box
CMD8-1U01-xxxxM	CWDM MUX DEMUX 8CH (xxxx-xxxx) With EXP And Monitor Port, Dual fiber, LC/UPC , Plug-in LGX Box (Customized)
1U02-2LGX	19" inch 1U rack with 2 slot for Plug-in LGX box, 440*230*44mm

**Note: We Support Customized Design, please contact us by email.**